

DIGITAL CAMERA SPECIFICATIONS		Canon PowerShot A630
<b>IMAGE SENSOR</b>		
	Type	1/1.8" CCD
	Effective Pixels	Approx.8.0M
	Colour Filter Type	Primary Colour
<b>IMAGE PROCESSOR</b>		
	Type	DIGIC II with iSAPS technology
<b>LENS</b>		
	Focal Length	7.3 – 29.2 mm (35mm equivalent 35-140 mm)
	Zoom	Optical 4x. Digital approx. 4x (with Digital Tele-converter approx. 1.6x or 2.0x and Safety Zoom (7)) (6). Combined approx. 16x
	Maximum f/number	f/2.8-f/4.1
	Construction	8 elements in 7 groups (2 aspherical elements)
<b>FOCUSING</b>		
	Type	TTL
	AF System/ Points	9-point AiAF, 1-point AF (Any position is available or fixed centre)
	AF Point Selection	Manual selection using FlexiZone AF/AE
	AF Lock	On/Off Selectable
	AF Assist Beam	Yes
	Manual Focus	Yes
	Closest Focusing Distance	1cm
<b>EXPOSURE CONTROL</b>		
	Metering modes	Evaluative, Centre-weighted average, Spot (centre or linked to focusing frame)
	AE Lock	Locked when shutter button is pressed half way
	Exposure Compensation	+/- 2 EV in 1/3 stop increments
	ISO Speed Equivalent	AUTO, High ISO Auto, 80, 100, 200, 400, 800
<b>SHUTTER</b>		
	Speed	15 – 1/2,500 sec (Available shutter speeds vary depending on the shooting mode)
<b>WHITE BALANCE</b>		
	Type	TTL
	Settings	Auto, Daylight, Cloudy, Tungsten, Fluorescent, Fluorescent H, Underwater, Custom
<b>VIEWFINDER</b>		
	Viewfinder	Real-image zoom, optical viewfinder
<b>LCD MONITOR</b>		
	Monitor	Vari-angle 2.5" P-Si TFT, approx. 115,000 pixels
	Coverage	100%
<b>FLASH</b>		
	Modes	Auto, Manual Flash On / Off
	Slow Sync Speed	Yes
	Red-eye Reduction	Yes
	Flash Exposure Compensation	+/- 2 EV in 1/3 stop increments
	Flash Exposure Lock	Yes
	Second Curtain Synchronisation	Yes
	Built-in Flash Range	45cm - 4.2m (W) / 3m (T) (at ISO AUTO equivalent)
	External Flash	Canon's High Power Flash HF-DC1
<b>SHOOTING</b>		
	Modes	Auto, Program AE, Shutter priority AE, Aperture priority AE, Manual, Custom, Portrait, Landscape, Night Scene, Stitch Assist, Movie, Special Scene (Night Snapshot, Kids & Pets, Indoor, Foliage, Snow, Beach, Fireworks, Underwater, Color Accent, Color Swap)
	Photo Effects	My Colors (My Colors Off, Vivid, Neutral, Sepia, Black & White, Lighter Skin Tone, Darker Skin Tone, Positive Film, Custom Color)
	Drive modes	Single, Continuous, Self-Timer
	Continuous Shooting	Approx. 1.8 fps (1) (until memory card becomes full) (2)
<b>RECORDING PIXELS / COMPRESSION</b>		
	Image Size	(L) 3264 x 2448, (M1) 2592 x 1944, (M2) 2048 x 1536, (M3) 1600 x 1200, (S) 640 x 480, (W) 3264 x 1832, (Postcard Date Imprint) 1600 x 1200
	Compression	Superfine, Fine, Normal
	Movies	(L)640 x 480, 30/15fps (M)320 x 240, 30/15fps (S)160 x 120, 15fps
	Movie Length	Up to 1GB or 1 hour (L and M). Up to 3 min (S) (2)
<b>FILE TYPES</b>		

	Still Image Type	JPEG compression, (Exif 2.2 [Exif Print] compliant) / Design rule for Camera File system, Digital Print Order Format [DPOF] Version 1.1 compliant
	Movies	AVI [Motion JPEG compression + WAVE (monaural)]
	Sound Files	WAVE (monaural)
<b>DIRECT PRINT</b>		
	Canon Printers	Canon SELPHY Compact Photo Printers and PIXMA Printers supporting PictBridge (ID Photo Print, Fixed Size Print and Movie Print supported on SELPHY CP & ES printers only)
	PictBridge	Yes
<b>OTHER FEATURES</b>		
	My Camera	Start-up image and camera sounds customisation
	Sound Memo	Up to 60 sec per image
	Intelligent Orientation Sensor	Yes
	Histogram	Yes
	Playback zoom	Approx. 2x – 10x
	Self Timer	Approx. 2 or 10 sec. or Custom
	Menu Languages	English, German, French, Dutch, Danish, Finnish, Italian, Norwegian, Swedish, Spanish, Simplified Chinese, Chinese (traditional), Japanese, Russian, Portuguese, Korean, Greek, Polish, Czech, Hungarian, Turkish, Thai, Arabic, Ukrainian, Romanian
<b>INTERFACE</b>		
	Computer	USB 2.0 Hi-Speed (Mini-B, PTP)
	Other	A/V output (PAL/NTSC)
<b>MEMORY CARD</b>		
	Type	Secure Digital (SD) Card or Secure Digital High-Capacity (SDHC) Card or MultiMediaCard (MMC), 16MB Memory card supplied
<b>SUPPORTED OPERATING SYSTEM</b>		
	PC	Windows 98SE / Me / 2000 SP4 / XP / XP SP1-2
	Macintosh	OS X v10.2 - 10.4
<b>SOFTWARE</b>		
	Browsing & Printing	ZoomBrowser EX / ImageBrowser
	Other	PhotoStitch
	Drivers	TWAIN (Windows 98 / 2000), WIA (Windows Me)
<b>POWER SOURCE</b>		
	Batteries	4x Size-AA Alkaline or NiMH Batteries(NB4-200) (Alkalines supplied)
	Battery life	Approx. 350shots (4) (with supplied batteries) Approx. 500 shots (with optional Canon NB-2AH batteries) (4) Approx. 20 hours. playback (with supplied batteries) Approx. 20 hours playback (with Canon NB-2AH batteries)
	A/C Power Supply	Optional, AC Adapter CA-PS500
<b>ACCESSORIES</b>		
	Case	Soft Case DCC-300
	Waterproof / Weatherproof Case	Waterproof Case (40m) WP-DC8 , Waterproof Case Weight WW-DC1
	Lenses	Conversion Lens Adapter, LA-DC58F Tele-Converter 1.75x TC-DC58N, Wide converter 0.7x WC-DC58N
	Flash	High Power Flash HF-DC1
	Power Supply & Battery Chargers	Battery Charger Kit CBK4-300, Ni-MH Batteries NB4-300, AC Adapter Kit ACK600
<b>PHYSICAL SPECIFICATIONS</b>		
	Operating Environment	0 – 40 °C, 10 – 90% humidity
	Dimensions (WxHxD)	109.4 x 66.0 x 49.1mm (excluding protrusions)
	Weight (body only)	Approx. 245g

All data is based on Canon standard testing methods except where indicated.  
Subject to change without notice.

- (1) Large/Fine with LCD monitor off
- (2) Depending on memory card speed / capacity
- (3) Compatible with all memory card capacities, including cards of 2GB and more
- (4) Based on the CIPA Standard and using the batteries and memory card format supplied with the camera, except where indicated
- (5) Not all functions of the flash are supported
- (6) Digital zoom available for still image and standard movie modes only. Optical zoom may not be available during movie recording
- (7) Depending on the image size selected