

Sony mylo - specs

LCD screen	2.4in QVGA (320x240), 65,536 colors
Keyboard	QWERTY
Internal memory	1GB Flash (a portion of which is used for data management functions)
Expansion	Memory Stick Pro Duo™ media Expansion Slot
Interface	DC IN 6V
	10 Pin Headphone/Microphone
	Hi-Speed USB (mini-B)
	Wireless LAN (IEEE 802.11b)1
Unit Dimensions	Approx. 4 7/8 x 31/32 x 2 1/2 inches (123 x 23.9 x 63 mm)
Unit Weight	Approx. 5.3 oz (150 g) including battery
Power requirements	AC power adaptor: DC 6 V
Battery	Removable Lithium-Ion Rechargeable Battery 3.7V 1200mAh
Battery operation time	Playing music: Up to 45 hours
	Talking: Up to 3.5 hours
	Viewing Web pages: Approx. 7 hours
	<i>(The times shown are measured using HP, "Auto Backlight Off" is set to "YES," and "Backlight Brightness" is set to "2." The times shown may vary depending on conditions of use, settings, and radio conditions)</i>
Operating temperature	5 to 35°C (41 to 95°F)
Applications	Instant Messaging: Yahoo!, Skype, Google
	Internet calling: Skype to Skype, Skype In, Skype Out
	Web Mail Clients: Yahoo!, Google
	Web Browser (Opera)
	Audio player
	Video player
	Photo viewer
	Text Editor
Wireless LAN Standard	IEEE 802.11b
Security	WEP (128-bit/64-bit) WPA-PSK (TKIP)
Modulation format	DS-SS (IEEE 802.11b compliant)
Communication range	Approx. 10m to 30m <i>(range may vary, depending on conditions of use and settings)</i>
Photo Supported formats	JPEG (DCF 2.0/Exif 2.21 compliant), PNG, BMP
Video Supported Codecs	MPEG-4 Advanced Simple Profile
	Audio Codec: MPEG-4 AAC-LC
	File Format: MP4 (Memory Stick Video Format compliant)
Audio Supported Codecs	MP3, ATRAC, WMA (Secured and Un-Secured)
Audio Supported bit rates	MP3: 32 to 320 kbps (supports variable bite rate (VBR))
	ATRAC: 48/64/96/128/132/160/192/256/320 kbps
	WMA: 32 to 320 kbps (supports variable bite rate (VBR))
Audio supported sampling frequencies	MP3: 32/44.1/48 kHz
	ATRAC: 44.1 kHz
	WMA: 44.1 kHz
Signal-to-noise ratio	80 dB
Speaker	Built in (for music-playback only - not speakerphone)
Microphone	Built in
External Headset Interface	10 pin connector for use included external mic adaptor and headphone jack (std mini stereo)
Frequency response	20 to 20,000 Hz
Supplied accessories	AC-ES608K3 AC Power Adaptor
	COMA-BP1 Lithium Ion Battery Pack
	MDR-000 Ear Bud Headphones
	000-000 Microphone/Headphone Adaptor
	Neoprene Slipcase
Supplied Software	mylo™ Utility
	SonicStage
UPC Code	0-27242-69268-8 (black), 0-27242-68684-7 (white)
Country of Origin	Japan